# **770**

# Nylon Protection Cable Chain with opening covers

6 m/s

30 m/s<sup>2</sup>

### Inner height (D) 51 mm

Double share Sideband & Frame construction with large anti-friction single-pin. Covers are opening from inner radius.

Vertical separators are available.

**Technical characteristics** when self-supported

For higher requirements please consult our

Speed

Acceleration

Separator	
- Unassembled	Part.no S770
- Assembled	Part.no S770MC

PG700	A C 2,5	51	78 ↓
700	<b>V</b>	ı	

Separator	
- Unassembled	Part.no S700
- Assembled	Part.no S700MC

Α	В	С	D	R	Weight/m	Chain
mm	mm	mm	mm	mm	kg	Part Number
120	78	85	51	150-200-250-300	3,30	770085 □□□ *
135	78	100	51	150-200-250-300	3,90	770100 🗆 🗆 🗆 *
185	78	150	51	150-200-250-300	4,10	770150 □□□ *
235	78	200	51	150-200-250-300	4,50	770200 □□□ *
285	78	250	51	150-200-250-300	5,00	70025 🗆 **

\*Complete the code by inserting the value of the radius (R): Ex. 770085 🗓 🗓 \*\*Complete the code by inserting the value of the radius (R): Ex. 70025 [1] Where: 0=150; 1=200; 2=250; 3=300

# LS :00000000000000000 70


11		14	141
mm	mm	mm	mm
150	378	260	615
200	478	310	770
250	578	365	930
300	678	410	1085

Length of chain (L) Half travel distance (LS) plus length of curve (M)

 $L = \frac{LS}{2} + M$ 

# Self-Supporting Capacity Diagram

The maximum length of the self-supporting capacity  $(\frac{LS}{2})$ in relationship to the weight of the cables and hoses contained per linear metre.



## **End Brackets**

The end brackets set allows the two ends of the chain to be attached to the equipment.






Fig. A
The chain can be fixed frontally, inner or outer radius. (Fig A)



The red marking in the diagram area considers the difference of weight between various widths of chain.

For applications with  $\frac{LS}{2}$ and weights not included in the area of the diagram showing self-supporting capacity, verify the possible use of support rollers (see page 30).



Chain	F
Туре	mm
770 C=85	100
770 C=100	115
770 C=150	165
770 C=200	215
700 C=250	265


## Nylon Type **Part Numbers**

\* Inner width (C)

complete S	et Assembled			
hain	End Brackets			
ype	Set			
70	AN770 □ □ □*KM			
00 C=250	AL700KM			
Complete Set Unassembled				
hain	End Brackets			
уре	Set			
70	AN770□□□*K			
00 C=250	AL700K			


### Serie Protection

770 **Nylon Protection Cable** Chain with opening covers



Separation System To choose the separators see page. 196

How to open the cover.



Special tool to remove the connecting pivots: Part Number PZ010.



For further information please consult Brevetti Stendalto's Technical Office